



All dimensions shown are in millimetres

- Test pressure: **12 BAR**
- Max working pressure: **8 BAR**
- Max working temperature: **100° C**
- All steel construction: **oval 60mm x 30mm x 1.5mm tubes
dia 25mm x 2mm headers**
- Connections: **½ inch BSP bottom opposite end tapings**
- Heat output determined in accordance with EN 442

Model	Output*	Output*	n	Water Content	Weight	Height	Length	Tapping Centres	Fixing Centres	
	ΔT=50K Watts	ΔT=60K Watts							V	H
PE 60-62	520	659	1.29	5.8	11	600	620	n/a	550	499
PE 60-83	696	882	1.29	7.8	14	600	830	n/a	550	709
PE 60-104	873	1105	1.29	9.7	17	600	1040	n/a	550	919
PE 150-27	470	595	1.29	6.5	11	1500	270	n/a	1450	149
PE 150-34	587	744	1.29	8.1	14	1500	340	n/a	1450	219
PE 150-41	705	892	1.29	9.7	16	1500	410	n/a	1450	289
PE 150-48	823	1041	1.29	11.3	19	1500	480	n/a	1450	359
PE 180-27	557	705	1.29	7.8	14	1800	270	n/a	1750	149
PE 180-34	696	882	1.29	9.7	16	1800	340	n/a	1750	219
PE 180-41	836	1058	1.29	11.6	19	1800	410	n/a	1750	289
PE 180-48	975	1244	1.29	13.6	24	1800	480	n/a	1750	359

* for chrome finish reduce shown output by 20%