

Uniclass L721113	EPIC H14/1
CI/SfB (74.449)	X

Traditional Pressalit design with new values. The nylon hinge-links are invisibly mounted, again leaving the inner sides of seat and cover with nothing but an even, smooth hygienic surface.



## Pressalit Tivoli 2®, incl. BN3 universal hinge

No. 316xxx-BN3999 with cover  
No. 315xxx-BU3999 without cover


### Design/Year

Pressalit, 2001, registered trade mark

### Product Description

PRESSALIT toilet seat with cover, model "Tivoli 2", art. no. 316 made of colour ingrained duroplast with stainless steel hinges.


- with BN3 universal hinge of stainless steel
- centre distance: 85 - 185 mm
- load - ring seat 240 kg
- with inlaid nylon hinge straps for easier cleaning
- suitable for many universal toilets
- 10 year guarantee



### Colour Programme xxx


With cover:  
000 white, 001 black (RAL 9005), 003 ivory, 013 bahamabeige, 052 manhattan, 073 champagne, 253 soft cream, 273 pergamon, 792 whisper grey

Without cover:  
000 white, 001 black



### Alternative Hinge

BA1 Fixed hinge  
B16 Top mounted hinge  
D07 Universal hinge for Sphinx "wandcloset 48 cm"  
BQ4 Universal toogle hinge



### Hinge Finish

999 Stainless steel

### Spare Parts

A4003 Buffer for pushing into cover, round, grey  
A4033 Buffer for pushing into seat, oval, grey  
A7223 End bush, barbed, long, grey  
A7224 End bush, barbed, for seat without cover, short, grey  
A9133 Set of straps and screws  
A9154 Set of straps and screws for seat without cover



Seats for your senses

**Product Weight** — Net weight approx. 2,900 kg, incl. hinge

<b>Packaging</b> —	Single carton	Dimensions:	Weight:
	5 single cartons in a master carton	449x381x64 mm	3,300 kg
	18 master cartons (90 seats) per pallet	456x388x340 mm	17,000 kg

**Material Description** — **TOILET SEAT:**  
The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

**BUFFERS:**  
EVA (copolymer made of ethylene and vinyl acetate).

**HINGE LINKS:**  
Metal version: Zinc with surface treatment. Plastic version: PA6 (polyamide).

**MOUNT/HINGES:**  
Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85.  
Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.

**Suitability List** — Usable on universal toilets - see the printed seat suitability specifications.

**Cleaning Instructions** — Use a mild soap solution. Seat and hinges should not be left damp, but be dried with a soft cloth. When using abrasive, corrosive or chlorine based cleaners for the bowl, avoid contact with seat and hinges. Therefore, when cleaning the bowl, make sure that seat and cover are in an upright position until all the cleaner has been flushed away.

The guarantee includes faults or defects in the material of our products within a period of 10 years.  
Products subject to minor technical modifications and design deviations E. & O.E.



[www.pressalit.com](http://www.pressalit.com)

European Sales Agencies  
Unit 10c Tanfield Lea (North) Industrial Estate  
Tanfield Lea, Stanley  
Co Durham, DH99UU  
Tel. 01207 236622, Fax 01207 236633  
info@europeansalesagencies.com  
www.europeansalesagencies.com

Pressalit A/S  
Pressalitvej 1  
DK-8680 Ry  
Tel. (+45) 8788 8788  
Fax (+45) 8788 8789  
pressalit@pressalit.com  
www.pressalit.com  
- a division of Pressalit Group A/S

