

Uniclass L721113	EPIC H14/1
CI/SfB (74.449)	X

Universal toilet seat in economy class.



Pressalit 1000, incl. BG4 fixed hinge

No. 304000-BG4999 with cover


Design/Year

Pressalit, 2001, registered design

Product Description

PRESSALIT toilet seat with cover, model "1000", art. no. 304 made of colour ingrained duroplast with stainless steel hinges.

- with BG4 fixed hinge of stainless steel
- centre distance: 155 mm
- load - ring seat 240 kg
- suitable for many universal toilets
- 10 year guarantee




Colour Programme

With cover:
000 white

Alternative Hinge

D16 Fixed hinge




Hinge Finish

999 Stainless steel

Spare Parts

- A4003 Buffer for pushing into cover, round, grey
- A4033 Buffer for pushing into seat, oval, grey



Product Weight

Net weight approx. 3,100 kg, incl. hinge



Seats for your senses

<i>Packaging</i>	<p>Single carton 5 single cartons in a master carton 18 master cartons (90 seats) per pallet</p>	<p>Dimensions: 454x382x62 mm 470x392x345 mm</p>	<p>Weight: 3,500 kg 17,800 kg</p>
<i>Material Description</i>	<p>TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. The body consists of approx. 50% urea (NH₂CONH₂), approx. 25% cellulose and approx. 25% formaldehyde (HCHO), as well as small amounts of various fillers and additives.</p> <p>BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).</p> <p>HINGE LINKS: Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.</p> <p>MOUNT/HINGES: Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.</p>		
<i>Suitability List</i>	Usable on universal toilets - see the printed seat suitability specifications.		
<i>Cleaning Instructions</i>	Use a mild soap solution. Seat and hinges should not be left damp, but be dried with a soft cloth. When using abrasive, corrosive or chlorine based cleaners for the bowl, avoid contact with seat and hinges. Therefore, when cleaning the bowl, make sure that seat and cover are in an upright position until all the cleaner has been flushed away.		
	<p>The guarantee includes faults or defects in the material of our products within a period of 10 years. Products subject to minor technical modifications and design deviations E. & O.E.</p>		



www.pressalit.com

European Sales Agencies
Unit 10c Tanfield Lea (North) Industrial Estate
Tanfield Lea, Stanley
Co Durham, DH99UU
Tel. 01207 236622, Fax 01207 236633
info@europeansalesagencies.com
www.europeansalesagencies.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: (+45) 8788 8788
Fax: (+45) 8788 8789
pressalit@pressalit.com
- a division of Pressalit Group A/S



Seats for your senses